

# Iridium Extreme 9575 Yellow



**Brand:** IRIDIUM  
**Product Code:** 11-103\_CPKTN1901-002  
**Availability:** 1

**Price: Fr. 1698.00**

**Ex Tax: Fr. 1570.77**

## Short Description

The waterproof and impact-resistant Iridium satellite mobile phone with GPS-supported emergency call function for extreme missions all over the globe.

## Description

The waterproof and impact-resistant Iridium satellite mobile phone with GPS-supported emergency call function for extreme missions all over the globe.

## Lieferumfang

- High performance battery 2'300 mAh
- Travel charger for mains operation incl. 5 adapters
- Mobile charger with lighter plug
- Protective cover
- USB data cable
- User Manual (English only)
- Quick Start Guide
- CD-ROM with software
- Accessory adapter (2x)
- Magnetic vehicle antenna with 1.5m cable
- Hand-free set with earphone and microphone

## Specifications

| Communication specs           |                                    |
|-------------------------------|------------------------------------|
| Antenna type                  | Teleskop ausziehbar                |
| Coverage                      | weltweit                           |
| Data transmission             | 2400 bit/s (komprimiert 9600 bit/s |
| Frequency range               | 1616.0 - 1626.5 MHz                |
| Provider                      | Iridium                            |
| Stand by time max.            | 30 h                               |
| Talking time max.             | 4 h                                |
| Construction / technical data |                                    |
| Capacity                      | 2'300 mAh @ 3.7 V                  |
| Data connection               | Mini-USB                           |
| DC power voltage              | 10-32 V=                           |
| Dimensions LxWxD              | 140 x 60 x 27 mm                   |
| Display type                  | LCD                                |
| Main power voltage            | 110-240 V~                         |
| Weight                        | 247 g                              |
| Environmental conditions      |                                    |
| Charging temperatures         | 0 °C bis +45 °C                    |
| Leak tightness                | IP65                               |
| Max. absolute altitude        | 12'192 m.ü.M = 40'000 ft           |
| Technical standards           | MIL-STD 810F                       |
| Temperature range             | -65 °C bis +71 °C                  |

## Product Gallery

